



As the original innovators who've pioneered, tested and introduced a sustainable, modular, cost-effective screening solution for the Aussie outdoors, we bring you the highest quality product. Correctly tested and engineered module sizes and formats, unique process and real product testing the only product to be treated with Decoshield™ protective stain system offer trade and DIYer a unique solution. Beware of imitations!

These comments are provided as a guide only. Like trellis and other landscaping materials, specific applications vary and responsibility remains with the installer. This is a DIY product, basic handyman/carpentry skills are required. Consult your local stockist or a landscaping professional if unsure.



Sustainable Timber

Made from Renewable Australian Hardwood tailings



Australian Made

Robust & Hardwearing All Australian Made & Owned



***Material Warranty**

10 Year Warranty *Read below.



Protective Stain System

Protected by Decoshield™ Penetrating Protective Stain System



Handy Sturdy Modules

1200mmx600mm sheets easy for DIY or trade transport carry and install. 9mm thk 4-5kg



Outdoor Grade

Hardwood product resistant to run-off weathering, bloat and rot



Ready-to-Install Easy to work with

Cut, fix, sand and paint or seal using standard handyman timberwork tools

- 10 YEAR WARRANTY against material rot, bloat or delamination under normal outdoor 'run-off' conditions. Screens mounted in vertical plain, not submerged/ constant contact with water, soil or chemicals. Installations are the responsibility of the installer. Directions herein must be followed.
- Hardwood Exteriorboard product, performs similarly to timber decking timber. It is resistant to normal run-off weathering, but not suitable for applications where submerged or <100mm to ground or constant water
- Natural Tannin may release and go rusty or grey over time(similar to merbau) if left unsealed. Like natural timber products the panels may vary in colour and texture.
- Painting is not required, however for alternative colours and finishes, use outdoor paint or deck sealer products, and follow instructions or consult landscaping prof.
- Suggested minimum fixing 300 centres apart along border.
- Alternatively use a suitable construction adhesive for invisible fixing, or use a combination of the screw and adhesive eg. neat decking screw in each corner and adhesive around border.
- For best results measure, drawup, pre-drill position and clamp before/during fixing. Use 2mm spacers to create a consistent joint with expansion joint, to allow for natural movement of timber materials.
- 45mm nominal border to accomodate typical fixing and conceal 90mm post or support.
- This is versatile product and can be cut down and fabricated as per timber, however this is not a freestanding structural product.



MAHJONG™



LEAF STREAM™



BUNGALOW™



NEST™



WOOLOOMAI™



MARA KESH™



LANTERN™



CUMULUS™



ORCHARD™



STAR ANAIS™

60% PRIVACY

80% PRIVACY (Privacy Compliant to most Codes)

90%+ PRIVACY High Privacy